

TPH_Q Series Booster Pump

50 Hz
Power: 370 - 1100 W
Head: Up to 56 M
Flow: Up to 160 L/min
Outlet: 1" - 1"
Inlet: 1" - 1 1/4"



Product Features

- Quiet Operation
- Easy installation
- Anti-cycling
- Dry-running protection
- Automatically starts and stops the pump based on demand

Applications

- Domestic water supply
- Air-conditioning system
- Automatic booster system
- Irrigation

Electrical Data 50Hz / Single Phase

Model	Power	Horse Power	Pipe Connection	Ampere	Rate / Max Head	Rate / Max Flow	Maximum Support Concurrent Usage
	W	HP	Inlet x Outlet				
TPH2T3KQ	370	1/2	1" x 1"	2.5	18 / 28	2.0 / 4.5	2x 2x
TPH2T4KQ	370	1/2	1" x 1"	2.9	27 / 38	2.0 / 4.5	2x 2x
TPH2T5KQ	550	3/4	1" x 1"	4.0	30 / 46	2.0 / 4.2	2 - 3x 2x
TPH2T6KQ	550	3/4	1" x 1"	4.3	40 / 56	2.0 / 4.2	2 - 3x 2x
TPH4T4KQ	750	1	1 1/4" x 1"	5.7	28 / 38	4.0 / 9.0	5x 4x
TPH4T5KQ	750	1	1 1/4" x 1"	6.9	35 / 46	4.5 / 9.0	5 - 6x 4x
TPH4T6KQ	1100	1 1/3	1 1/4" x 1"	7.7	30 / 56	7.0 / 9.6	6x 4x

Performance Curve

